

SECTION VI: ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:

Small spills - Pick up with absorbent material and place in drum for disposal.

Large spills - Divert to holding area and let dry. Allow to dry and dispose of as non-hazardous waste.

Clean up equipment and spills before product dries.

SECTION VII: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Respiratory Protection (Specify Type): Not required for most conditions. Use mist respirator in enclosed areas.

Ventilation: Local exhaust: not required; Mechanical (General): Not required.

Protective Gloves: Use rubber gloves.

Eye Protection: Use chemical splash goggles.

Other Protective Clothing and Equipment: Wear body-covering clothing.

Work/Hygienic Practices: Wash hands/exposed skin after use. Remove contaminated or wetted clothing.

SECTION VIII: PHYSICAL/CHEMICAL PROPERTIES

Boiling Point:	212° F
Vapor Pressure (MM HG):	N/A
Vapor Density:	N/A
Solubility in Water:	100% Dispersible
Appearance and Odor:	Thin, milky white/beige liquid with mild odor
Specific Gravity:	1.02 (water = 1)
Melting Point:	N/A
Evaporation Rate:	N/A
Volatile Organic Compounds (VOC's):	60 g/L

SECTION IX: STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Store between 3° C (38° F) and 41° C (105° F). Avoid direct sunlight. Shelf life 2 years. Keep from freezing. Store in closed containers. Keep unused product in original container to avoid converting unused material.

Incompatibility (Materials to avoid): Alkalis, ammonia, iron compounds, oxidizing agents, chromates (pickling agents), some latex (tannin staining). See Technical Data.

Hazardous Decomposition or By-Products: Carbon monoxide, organic acids and aldehydes.

Hazardous Polymerization: Will not occur.

SECTION X: DISPOSAL CONSIDERATIONS

Waste Disposal Method: This primer may be allowed to dry and disposed of as a non-hazardous, solid waste.

SECTION XI: TRANSPORT INFORMATION

US DOT Class: 55 - No shipping restrictions. May be shipped normally as a non-hazardous material.

UN Harmonized Code: 3810.10.0000

Tariff Code: 149980.2

Prepared by Acrylabs, Inc.- Technical Department 5/11/05

The information contained herein relates only to the specific material identified and is believed to be accurate and reliable by all those associated with Acrylabs, Inc. No representations, guarantee or warranty, expressed or implied, is made as to the accuracy, reliability, or completeness of the information provided. Users assume all risks associated with the use of the material and are advised to confirm in advance that the information contained in this MSDS is correct, applicable, and suitable to their circumstances. In accordance with the OSHA Federal Hazard Communication Standard, the actual percentages of ingredients have been omitted.