



MESH 2000

PRODUCT DATA

MESH 2000 is a high strength, stitchbonded, reinforcement fabric for fluid or cold-applied roofing systems. ***MESH 2000*** is lightweight and flexible, yet tough and durable. ***MESH 2000*** offers advantages over traditional roofing such as fiberglass and organic felts. Conformability, elongation, lightweight, UV resistant, and strength are a few of the benefits.

MESH 2000 is available in various sizes:

40" Inch X 324' feet (allow 3" inch overlap = 1,000 Square Feet)

18" Inch X 300' feet

12" Inch X 300' feet

6" Inch X 300' feet

4" Inch X 300' feet

Technical Data:

Weight: 3 .oz per sq. ft.

Tensile Strength: 57 lbs.

Elongation: 61.6%

Mullen Burst: 176.8 lbs.

Tear Strength: 16.1 lbs.

Installation: Apply **2100B** at a minimum rate of 1.5 gallons per 100 sq. ft., immediately embed **Mesh 2000** into wet coating making sure the fabric is tight to the surface, avoiding wrinkles and fishmouths. Apply saturation coat of **2100B** at a minimum rate of 1.5 gallons per sq. ft., achieving a base membrane thickness of 30 mils.

730 Commercial Lane, Honey Brook, PA 19344

Toll Free (866)273-1355, Fax (610)273-1357

www.acrylabs.com