



Renewable Roof Systems
Deck Membranes

Acrycrete

PRODUCT DATA

Description: **Acrycrete** is designed for refinishing and water-proofing all types of surfaces including decks, walk-ways, drivable surfaces, foundation walls, interior & exterior basement walls, moisture-retaining structures such as pools, cisterns, and concrete shrubbery boxes. Reinforcing it with the Acrylabs Reinforcement Fabric will create a hard-wearing, waterproof membrane that is also resistant to standing water and ideal for subterranean waterproofing.

Application: Mix for 1 minute or until all powder is dissolved. Batch will be a thin, slurry-like consistency. Using a roof brush, apply a generous amount of **Acrycrete** to clean dry surface.

TECHNICAL DATA

Admixture:

WEIGHT PER DUECE	16 LBS	ASTM D-1475
% SOLIDS BY WEIGHT	57.0%	ASTM D-1644-A
VISCOSITY @ 25°C, cPs	≤60	
V.O.C.	≤50 g/l	ASTM D3960-01
pH	7-8	ASTM E70-97
FLASH POINT	N/A	
Tg, °C (Calculated)	13	
(MFFT), °C	11	

Portland Type I & II

Portland Cement complies with ASTM C 150 Type I and in many locations also complies with ASTM C 150 Type II

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.