



Renewable Roof Systems  
Deck Membranes

## Acrypel

### PRODUCT DATA

**Description:** **Acrypel** is a high quality, acrylic water repellent that is formulated for maximum durability and adhesion. **Acrypel** can be applied to new or restored surfaces, high porosity concrete, split face block, brick, adobe, limestone, granite, sandstone, terra cotta, stuccos & mortar. **Acrypel** is an excellent block sealer and can be used on most vertical or horizontal exterior and above grade masonry surfaces. **Acrypel** performs well in a variety of climates and temperatures. **Acrypel** is environmentally friendly and safe for plants and animals.

**Application:** **Acrypel** can be brushed, rolled, or sprayed (Hudson type Sprayer recommended). Application rate will vary with the porosity of the surface. Allow two to four hours between coats. Dry time will vary depending on temperature, humidity, and ventilation.

**Coverage:** Approximately 50 - 100 square foot per gallon depending on surface porosity.

**Acrypel** is available in 1 and 5 gallon plastic containers.

**Precautions:** **Acrypel** water-based products. Avoid contact with skin and eyes. In case of contact, immediately flush with clear water. For eyes, get medical attention in addition to flushing. Avoid inhalation of spray mist. If spray mist is inhaled, immediately contact a physician. Wear rubber gloves, coveralls, and safety goggles when applying.

### TECHNICAL DATA

WEIGHT PER GALLON	7.84 LBS
FINISH	CLEAR
VISCOSITY	SIMILAR TO WATER
V.O.C.	50.6g/l (.422 # / gallon)
SOLIDS BY VOLUME	10%
SERVICE TEMPERATURE LIMIT	N/A
FLASH POINT	NONE
SHELF LIFE	1 YEAR
CLEAN UP	SOAP & WATER

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.