



Renewable Roof Systems  
Deck Membranes

## Metal Prep Rust Inhibitive Primer

### PRODUCT DATA

**Description:** **Rust Inhibitive Primer** is a water borne, highly effective acrylic paint used to prime rusted metal. Utilizing advanced technology,

**Rust Inhibitive Primer** is formulated for maximum adhesion to ferrous and galvanized metals and provides excellent surface corrosion protection prior to application of Acrylabs roof membranes.

**Application:** Can be brushed, rolled, or sprayed. Final thickness of **Rust Inhibitive Primer** will vary depending on surface conditions. **Rust Inhibitive Primer** should be applied at 200-250 square feet per gallon to achieve the suggested dry film thickness of 2 - 3 mils (DFT). It can also be used to spot prime rust as needed.

**Rust Inhibitive Primer** is available in 1 and 5 gallon plastic containers.

### TECHNICAL DATA

WEIGHT PER GALLON	10.8 LBS.
FINISH	Low Sheen
V.O.C.	<0.83 lbs./gal (100g/l)
SOLIDS BY VOLUME	39%
SERVICE TEMPERATURE LIMIT	180 F
FLAME SPREAD RATING	N/A
FLASH POINT	200 F, Seta Flash
SHELF LIFE	1 YEAR
CLEAN UP	SOAP & WATER

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.