



Liquid Roofing Products

Finish Coat

PRODUCT DATA

Description: **Finish Coat** is a water borne, 100% acrylic coating and is a component of the fully reinforced and partially reinforced Acrylabs roof membrane. Utilizing advanced technology, **Finish Coat** is formulated for maximum adhesion to new construction such as plywood, OSB, ISO, EPS and other roof sheathing as well as asphalt, metal, modified bitumen, concrete, wood, EPDM, fiberglass, and most single ply membrane systems. **Finish Coat** cures to a strong, durable finish that is easily maintained and is used as the final coats for Acrylabs Roof Systems.

Finish Coat is available in other colors.

Application: Can be brush, roll, or spray applied. A uniform dry film thickness of 10 mils (DFT) per coat, two coats minimum, is required to maintain a pinhole free membrane. Final thickness of Finish Coat may vary depending on surface conditions (porosity, texture, etc.). Allow enough time to dry to the touch before recoating.

Finish Coat is available in 5- and 55-gallon plastic containers.

TECHNICAL DATA

WEIGHT PER GALLON	12 LBS	ASTM D-1475
% SOLIDS BY WEIGHT	67.0%	ASTM D-1644-A
% SOLIDS BY VOLUME	53%	ASTM D-2697
PIGMENT VOLUME	43.0%	
VISCOSITY (Brookfield)	130-140 Ku	ASTM D-562-A
V.O.C.	<50 g/l	ASTM D3960-01
PH	8.6 -9.2	ASTM E70-97
FLASH POINT	N/A	
LOW TEMPERATURE FLEXIBILITY	Mandrel Bend @ -57F	ASTM D522-93A
ELONGATION AT (break)	196% @ 73F	ASTM D-2370
TENSILE STRENGTH AT (psi)	236psi @ 73F	ASTM D-2370
WATER SWELLING	9.2	ASTM-D 471
FUNGI RESISTANCE	ZERO RATING	G-53
PERMEABILITY (20MILS)	21.9 PERMS	ASTM D1653
ACCELERATED WEATHERING	NO EFFECT 2 YEARS	ASTM G-53

For more detailed instructions, refer to our Installation Guide or consult Acrylabs Corporate Office.